

# WE DELIVER

June 24, 2024




San Francisco  
**Water Power Sewer**

Services of the San Francisco Public Utilities Commission



# Precipitation at Hetch Hetchy Water Year 2023



A new water year (WY) starts every October. The graph charts cumulative precipitation at Hetch Hetchy Reservoir as the WY progresses. Precipitation is shown as a percentage of average, and curves for the current year and past year are shown. Cumulative precipitation curves for both dry and wet years are also shown, as well as a median. Why 1977? – It is the driest year on record. Why 1983? – It is the wettest year on record.



# Reservoir Storage Levels

Storage as of: 24-Jun-2024

An acre foot is the volume of one acre of surface area (150 by 290 feet — 10 feet shorter than a football field) to a depth of one foot, also equal to approximately 325,851 gallons.

On average, 1 acre foot of water is enough to meet the demands of 4 people for a year. Tuolumne System storage includes Hetch Hetchy, Cherry (Lloyd), and Eleanor Reservoirs.

Local system includes Crystal Springs, Calaveras, San Antonio, San Andreas, and Pilarcitos Reservoirs.

Reservoir	Current Storage <sup>1,2,3</sup> (AF)	Maximum Storage <sup>4</sup> (AF)	Available Capacity (AF)	Percent of Maximum Storage	Normal Percent of Maximum Storage <sup>5</sup>
<b>Tuolumne System</b>					
Hetch Hetchy	360,800	360,360	0	100.0%	99.0%
Cherry	268,900	273,345	4,445	98.4%	-
Eleanor	26,860	27,100	240	99.1%	-
Water Bank	570,000	570,000	0	100.0%	100.0%
<b>Total Tuolumne Storage</b>	<b>1,226,560</b>	<b>1,230,805</b>	<b>4,685</b>	<b>99.7%</b>	<b>-</b>
<b>Local System</b>					
Calaveras	94,019	96,670	2,651	97.3%	-
San Antonio	50,614	53,266	2,652	95.0%	-
Crystal Springs	51,651	68,953	17,302	74.9%	-
San Andreas	11,599	18,675	7,076	62.1%	-
Pilarcitos	2,319	3,125	806	74.2%	-
<b>Total Local Storage</b>	<b>210,202</b>	<b>240,689</b>	<b>30,487</b>	<b>87.3%</b>	<b>-</b>
<b>Total System Storage</b>	<b>1,436,762</b>	<b>1,471,494</b>	<b>35,172</b>	<b>97.6%</b>	<b>89.6%</b>
<b>Total without water bank</b>	<b>866,762</b>	<b>901,494</b>	<b>35,172</b>	<b>96.1%</b>	<b>-</b>

<sup>1</sup> Upcountry storage is the date's BAM storage value taken from USGS data

<sup>2</sup> Water bank storage reported by HHWP for 06/23/2024

<sup>3</sup> Local storage is the date's BAM storage value taken from USGS data


<sup>4</sup> Hetch Hetchy maximum storage is with drum gates activated. Cherry and Eleanor maximum storage is with flashboards in. All maximum storages taken from rating curve.

<sup>5</sup> The ratio of median storage for this day over maximum storage capacity. Median storage for this day is based on historical storage data from years 1991 - 2020

# Total Deliveries – Total Service Area

--- Provisional Data Subject to Revision ---

SFPUC Regional Water System - Meter Deliveries  
Total SFPUC Service Area  
Source: SFPUC Regional Water System County Meters




We provide water to 2.7 million residents in the greater Bay Area. Our total service area includes customers in the City and County of San Francisco; as well as Wholesale customers in the Peninsula, South Bay, and East Bay Communities.



# Total Deliveries – SF Customers

— Provisional Data Subject to Revision —

SFPUC Regional Water System - Meter Deliveries  
San Francisco Customers  
Source: SFPUC Regional Water System County Meters




We provide water to 2.7 million residents in the greater Bay Area. "San Francisco Customers" include water metered at the San Francisco County Line, which serves customers in the City and County of San Francisco.



# Photovoltaic Gen & Metered Cogeneration

## PV Generation and Metered Cogeneration

21 Jun 2024



Note: SEP Cogen has been running intermittently this year

Solar Photovoltaic (PV) technology uses semiconductors to convert solar radiation into DC Electricity. Cogeneration is the process of capturing and using the by-products of electrical generation or wastewater treatment facilities. In the case of wastewater treatment facilities, cogeneration systems use the anaerobic digester gas to generate electricity. Rather than directly releasing these by-products back into the environment, they can be used to generate electricity for the facility.


\*MW=megawatts\*



# Hydro Generation & Municipal Load

## Hydro Generation and Municipal Load

21 Jun 2024



**Municipal load is the amount of energy needed to power our municipal facilities. On average that is about 120 MW. These facilities include the San Francisco Municipal Railway, SF General Hospital, SF Unified School District, SFO, SFPD, SFFD, the Port of SF, and the SFPUC's regional and local water and wastewater systems. Hydropower is produced at Kirkwood, Moccasin, and Holm powerhouses.**